Preparation of High Photocatalyst Mesoporous TiO₂ from Nanosheets Using Autoclave Unit (Thai Made)

A. Simpraditpan, T. Wirunmongkol, W. Boonwatcharapunsakun, S. Sakulkhaemaruethai, S. Pivsa-art, C. Duangduen and S. Pavasupree

Abstract— The aim of this study is to prepare mesoporous TiO_2 from high specific surface area nanosheets by simple hydrothermal method at 120 °C of 12 hrs using autoclave unit (Thai made). The shape, size (TEM), crystalline structure (XRD), BET-specific surface area and photocatalytic activity of the prepare samples were investigated. The XRD results revealed that the prepared nanosheets were amorphous phase. The specific surface area, average pore diameter and pore volume were 360.28 m^2/g , 3-5 nm and 0.275 cm^3/g , respectively. The crystalline structure of calcined nanosheets at 300-600 °C was anatase TiO_2 with decreasing in the specific surface area. The intensity of anatase TiO_2 structure increased when the calcination temperature was increased. Moreover, the photocatalytic activity of the calcined nanosheets was higher than the as-synthesized nanosheets and commercial nano TiO_2 (P-25, JRC-01, JRC-03). This preparation method provided a simple routh to fabricate nanosheets using autoclave unit (Thai made).

Keywords— Hydrothermal, Nanosheet, Photocatalytic Activity, Titanium Dioxide

1. INTRODUCTION

Titania materials or TiO_2 and TiO_2 -related materials are of importance for utilizing solar energy and environmental purification. TiO_2 has been widely used for various applications such as a semiconductor in dye-sensitized solar cell, water treatment materials, catalysts and gas sensors [1-6].

From the earlier study exhibited two types only of crystalline (rutile and anatase) measured in photocatalytic, the rutile was not adequate in order to catalyst because high recombination of electron and hole than anatase as a result the photocatalytic activity was poor [7-14]. In our previous work, high specific surface area nanosheets were synthesized via hydrothermal method [15].

In this study, the preparation of anatase mesoporous TiO_2 from high specific surface area nanosheets by hydrothermal method using Teflon-lined stainless steel autoclave (Thai made) was investigated. The shape, size, crystalline structure, BET-specific surface area and photocatalytic activity of the prepared samples were characterized.

2. EXPERIMENTAL PRECEDURE

2.1 Preparation of nanosheets

Nanosheets were prepared via hydrothermal method using titanium (IV) butoxide mixing with acetylacetone in a Teflon-lined stainless steel autoclave that was designed and built of Rajamangala University of Technology Thanyaburi (RMUTT) (Fig.1). Distilled water (80 ml) and NH₃OH were added into the solution and stirred about 5 minutes, then the autoclave was heated at 120 °C and stirring for about

12 hrs. After that, the mixture was cooled at room temperature. In the last, the product was filtered and washed by the 0.1 M of HCl and the distilled water for several times.

The synthetic material was dried in the oven at 100 $^{\circ}$ C for 12 hrs. The prepared sample was heated at 300, 400, 500, 600, 700 and 800 $^{\circ}$ C for 2 hrs.

2.2 Characterizations

The crystalline structure of the samples was evaluated by X-ray diffraction (XRD, X'Pert PRO MPD model pw 3040/60, PANalytical). The microstructure of the prepared materials was analyzed by transmission electron microscopy (TEM, JEM-2100, JEOL). The Brunauer-Emmett-Teller (BET, BELSORP-Mini, Rubotherm) specific surface area was determined by the nitrogen adsorption (BELSORP-Mini, Rubotherm).



Fig.1. Teflon-lined stainless steel autoclave.

2.3 Photocatalytic activity measurement

Photocatalytic activity was measured the concentration of I_3^- that generated from photo-oxidation reaction of I which transformed into I_2 in excess of Icondition [16] following Eqs. (1) and (2).

$$2 I^{-} \qquad \longrightarrow \qquad I_{2} + 2e^{-} \qquad (1)$$

$$I_2 + I^+ \longrightarrow I_3^-$$
 (2)

A. Simpraditpan, T. Wirunmongkol, W. Boonwatcharapunsakun S. Pavasupree and S. Pivsa-art are with the Department of Materials and Metallurgical Engineering, Faculty of Engineering, Rajamangala University of Technology Thanyaburi, Klong 6, Thanyaburi, Pathumthani 12110, Thailand, E-mail: sorapongp@yahoo.com.

S. Sakulkhaemaruethai and C. Duangduen are with the Department of Chemistry, Faculty of Science, Rajamangala University of Technology Thanyaburi, Klong 6, Thanyaburi, Pathumthani 12110, Thailand

The 50 mg of TiO₂ powders and potassium iodide solution was filled into a cylindrical vessel. After that, it was placed on obscure condition, and 15 W of UV light was illuminated with stirring condition at room temperature for 1 hour after that the solution was separated by centrifuge method and it was diluted for 10 times order to measured of ion by light absorption of 288 nm using UV–vis spectrometer, the coefficient of the intensity from the experimental was 4.0×10^4 cm mol/l.

3. RESULT AND DISCUSSION

3.1 Characterization

The XRD pattern of the prepared sample showed amorphous-like structure (Fig. 2). The calcined samples of 300-600 °C of 2 hrs were anatase phase. The anatase TiO₂ structure increased when the calcination temperature was increased. The peaks were rather sharp, which indicated the calcined nanosheet TiO₂ had relatively high crystallinity. The peaks corresponding to rutile TiO₂ appeared at 700 °C and almost showed rutile TiO₂ structure at 800 °C [17].



Fig.2. The XRD patterns of as-synthesized nanosheets and calcined nanosheets at various temperatures (A: anatase and R: rutile).

The BET specific surface area, pore diameter and pore volume of nanosheet were about 360.28 $m^2\!/g,\,3\text{-}5$ nm and 0.275 cm³/g, respectively. The result of microstructure showed that the as-synthesized sample was nanosheets-like structure. The prepared nanosheets were roll, twist and agglomerate (fig.3). The nanosheets transformed to nanoparticles (fig. 4 (a)) when heated at 300-800 °C. The increasing of calcination temperatures, indicating the grain growth of TiO₂ crystallites [18] (fig. 4 (b)-(f)). The BET specific surface area of the calcined nanosheets at 300, 400 and 500 °C were about 108.93, 71.24 and 46.77 m²/g, respectively. The BET specific surface area decreased with increasing calcination temperature, resulting in the increasing of pore diameter and decreasing of pore volume, became the nanosheets structure after calcinations were destroyed and changed to nanoparticles composite at high temperature [15, 19-20].



Fig.3. TEM images of as-synthesized nanosheets TiO_2 (a) x 40,000 and (b) x 100,000 magnified.



Fig.4. TEM images of the nanosheets TiO_2 calcined at various temperatures for 2 hrs (a) 300 °C, (b) 400 °C, (e) 500 °C, (d) 600 °C, (e) 700 °C and (f) 800 °C.

3.2 Photocatalytic activity

The calcined nanosheets TiO_2 (excepted at 800 °C) showed higher I_3^- concentration than the as-synthesized sample. The calcined nanosheets TiO_2 at 300 °C for 2 hrs showed the highest activity and also higher than commercial nanoparticle TiO_2 samples (P-25, JRC-01, JRC-03) due to the exist of mesoporous structure with high specific surface area and anatase phase [7, 18, 21].



Fig.5. Photocatalytic activity (I_3^- concentration) of the as-synthesized nanosheets, the calcined nanosheets and commercial nano TiO₂ samples (P-25, JRC-01, JRC-03).

6. CONCLUSION

Nanosheet TiO₂ was prepared by hydrothermal method at 120 °C for 12 hrs with a Teflon-lined stainless steel autoclave (Thai made). The as-synthesized nanosheets TiO₂ showed amorphous structure. The BET specific surface area, pore diameter and pore volume of the nanosheets TiO₂ were about 360.28 m²/g, 3 nm and 0.275 cm³/g, respectively. The calcined nanasheets had higher photocatalytic activity than the as-synthesized sample and the commercial nano TiO₂ powder (P-25, JRC-01, JRC-03). This preparation method provided a simple routh to fabricate nanostructures TiO₂ with high photocatalytic activity.

ACKNOWLEDGMENT

This research was supported by office of National Research Council of Thailand (NRCT) and Nanotechnology for Textile and Polymer Research Group (NanoTeP) of Faculty of Engineering of Rajamangala University of Technology Thanyaburi.

REFERENCES LIST

- [1] Fujishima, A.; Rao, T.N. and Tryk, D.A. 2000.Titanium dioxide photocatalysis. *Journal of Photochemistry and Photobiology C: Photochemistry Reviews* 1(1): 1-21.
- [2] Grätzel, M. 2001. Photoelectrochemical cells. *Nature* 414(6861): 338-344.
- [3] Ngamsinlapasathian, S.; Sreethawong, T.; Suzuki, Y. and Yoshikawa, S. 2005. Single and double-layered mesoporous TiO₂/P25 TiO₂ electrode for dye-sensitized solar cell. *Solar Energy Materials and Solar Cells* 86(2): 269-282.
- [4] Pavasupree, S.; Suzuki, Y.; Pivsa-Art, S. and Yoshikawa, S. 2005. Preparation and characterization of mesoporous MO₂ (M=Ti, Ce, Zr, and Hf) nanopowders by a modified sol-gel method. *Ceramics International* 31(7): 959-963.
- [5] Pavasupree, S.; Suzuki, Y.; Pivsa-Art, S. and Yoshikawa, S. 2005. Preparation and characterization of mesoporous TiO₂–CeO₂ nanopowders respond to visible wavelength. *Journal of Solid State Chemistry* 178(1): 128-134.

- [6] Sreethawong, T.; Suzuki, Y. and Yoshikawa, S. 2005. Synthesis, characterization, and photocatalytic activity for hydrogen evolution of nanocrystalline mesoporous titania prepared by surfactant-assisted templating sol-gel process. *Journal of Solid State Chemistry* 178(1): 329-338.
- [7] Sakulkhaemaruethai, S.; Pavasupree, S.; Suzuki, Y. and Yoshikawa, S. 2005. Photocatalytic activity of titania nanocrystals prepared by surfactant-assisted templating method—Effect of calcination conditions. *Materials Letters* 59(23): 2965-2968.
- [8] Augustynski, J. 1993. The role of the surface intermediates in the photoelectrochemical behaviour of anatase and rutile TiO₂. *Electrochimica Acta* 38(1): 43-46.
- [9] Zhao, X.-T.; Sakka, K.; Kihara, N.; Takada, Y.; Arita, M. and Masuda, M. 2005. Structure and photo-induced features of TiO₂ thin films prepared by RF magnetron sputtering. *Microelectronics Journal* 36(3-6): 549-551.
- [10] Kiyono, M. 1991. *Titanium Dioxide*, Gihoudou Publishers.
- [11] Song, X.-M.; Wu, J.-M.; Tang, M.-Z.; Qi, B. and Yan, M. 2008. Enhanced photoelectrochemical response of a composite titania thin film with single-crystalline rutile nanorods embedded in anatase aggregates. *Journal of Physical Chemistry C* 112(49): 19484-19492.
- [12] Wang, P.; Zhai, Y.; Wang, D. and Dong, S. 2011. Synthesis of reduced graphene oxide-anatase TiO₂ nanocomposite and its improved photo-induced charge transfer properties. *Nanoscale* [On-line serial], Retrieved April 1, 2011 from the World Wide Web: http://pubs.rsc.org/en/Content/ArticleLanding/2011/NRc 0nr00714e.
- [13] Li, C.; Liang, B.; Song, H.; Xu, J.-Q. and Wang, X.-Q. 2008. Preparation of porous rutile titania from ilmenite by mechanical activation and subsequent sulfuric acid leaching. *Microporous and Mesoporous Materials* 115 (3): 293-300.
- [14] Yu, J.-G. and Wang, G.-H. 2007. Effects of hydrothermal temperature and time on the photocatalytic activity and microstructures of bimodal mesoporous TiO₂ powders. *Applied Catalysis B: Environmental* 69(3): 171-180.
- [15] Pavasupree, S.; Ngamsinlapasathian, S.; Suzuki, Y. and Yoshikawa, S. 2007. Preparation and characterization of high surface area nanosheet titania with mesoporous structure. *Materials Letters* 61(14-15): 2973-2977.
- [16] Adachi, M.; Murata, Y.; Okada, I. and Yoshikawa, S. 2003. Formation of titania nanotubes and applications for dye-sensitized solar cells. *Journal of the Electrochemical Society* 150(8): G488-G493.
- [17] Pavasupree, S.; Ngamsinlapasathian, S.; Suzuki, Y. and Yoshikawa, S. 2006. Synthesis and dye-sensitized solar cell performance of nanorods/nanoparticles TiO₂ from high surface area nanosheet TiO₂. *Journal of Nanoscience and Nanotechnology* 6(12): 3685-3692.
- [18] Jitputti, J.; Pavasupree, S.; Suzuki, Y. and Yoshikawa, S. 2007. Synthesis and photocatalytic activity for watersplitting reaction of nanocrystalline mesoporous titania prepared by hydrothermal method. *Journal of Solid State Chemistry* 180(5): 1743-1749.
- [19] Tsai, C.-C. and Teng, H. 2004. Regulation of the physical characteristics of titania nanotube aggregates synthesized from hydrothermal treatment. *Chemistry of Materials* 16(22): 4352-4358.

9th Eco-Energy and Materials Science and Engineering Symposium, Chiang Rai, Thailand, 25-28 May 2011

- [20] Yoshida, R.; Suzuki, Y. and Yoshikawa, S. 2005. Effects of synthetic conditions and heat treatment on the structure of partially ion-exchanged titanate nanotubes, *Materials Chemistry and Physics* 91 (2-3): 409-416.
- [21] Jitputti, J.; Suzuki, Y. and Yoshikawa, S. 2008. Synthesis of TiO₂ nanowires and their photocatalytic activity for hydrogen evolution. *Catalysis Communications* 9(6): 1265-1271.